

Harbil NSC Series

Fluid Management continues to offer manual dispensers that stand the test of time. The Harbil NSC Series is equipped with Teflon® piston seals for extended life on important wear components, and the 50- and 80-ounce capacity canisters are convenient to fill and clean. Sawtoothed, self-zeroing gauges provide accuracy for any increment of colorant and are mounted outside of the pump tube for easy reading and maintenance. Dispensers are available in countertop, floor model and in-line styles. In addition, solvent-compatible components are available.



The NSC Series

Features sawtoothed, self-zeroing gauges to reduce errors and prevent mis-tints.



Come out on top

The tabletop or mixer stand designs are ideal solutions to meet tight space constraints.



Line them up

The NSC in-line model makes queuing large orders easy.

TEFLON® is the registered trademark of E. I. du Pont de Nemours and Company or its affiliates.

Service



Fluid Management products are backed by FM Direct, our nationwide team of phone and field service engineers. Providing you with local, hands-on support, over 30 factory-direct service technicians deliver expertise when and where you need it.

- 24/7 multilingual tech support
- Fully stocked parts inventory on FM Direct vans
- Extended warranty and preventive maintenance programs

Specifications

	Blendorama®		Harbil® NSC		Dual Pump
	25	53	50	80	Dual Pump
Dispensing:	Piston Pump	Piston Pump	Piston Pump	Piston Pump	Piston Pump
Pump Capacity:	2 oz. + 1/8 oz.	5 oz. + 1/8 oz.	1 oz.	2 oz.	5 oz.
Accuracy (Min. Dispense):	1/384th oz.	1/384th oz.	1/128th oz.	1/128th oz.	1/128th oz.
Canister Capacity:	84 oz. (2.6 quarts)	84 oz. (2.6 quarts)	50 oz. (1.6 quarts)	80 oz. (2.5 quarts)	192 oz. (6 quarts)
Canister Material:	Solvent-Resistant Plastic	Solvent-Resistant Plastic	Solvent-Resistant Plastic	Stainless Steel	Stainless Steel
Shelving:					
Turntable Counter:	—	—	Quart and 1-gallon		Quart and 1-gallon
Turntable Floor:	Quart, 1-gallon & 5-gallon		Quart, 1-gallon & 5-gallon		Quart, 1-gallon & 5-gallon
In-line:	—	—	Quart, 1-gallon & 5-gallon		Quart, 1-gallon & 5-gallon
Nozzle Closer:	Sniffback™ and self-sealing wiper blades		—	Optional	Optional
Colorant Compatibility:	Universal, Waterborne, Organic, Solvents		Universal, Waterborne, Organic, Solvents		Universal, Waterborne, Organic, Solvents
Stands:					
Turntable Counter:	—	—	10-12 Canisters: 25"D x 21"H, 13-16 Canisters: 31"D x 21"H	10-12 Canisters: 25"D x 27"H, 13-16 Canisters: 36"D x 27"H	10-12 Canisters: 34"D x 34"H, 13-16 Canisters: 42"D x 34"H
Turntable Floor:	11-12 Canisters: 30"D x 54"H, 14-16 Canisters: 32"D x 54"H	9-12 Canisters: 30"D x 54"H, 14-16 Canisters: 32"D x 54"H	10-12 Canisters: 25"D x 57"H, 13-16 Canisters: 31"D x 57"H	10-12 Canisters: 25"D x 63"H, 13-16 Canisters: 36"D x 63"H	10-12 Canisters: 34"D x 65"H, 13-16 Canisters: 42"D x 65"H
In-line:	—	—	10 Canister: 48"W x 20"D x 54"H, 12 Canister: 54"W x 20"D x 54"H, 14 Canister: 63"W x 20"D x 54"H, 16 Canister: 72"W x 20"D x 54"H	10 Canister: 48"W x 20"D x 54"H, 12 Canister: 54"W x 20"D x 54"H, 14 Canister: 63"W x 20"D x 54"H, 16 Canister: 72"W x 20"D x 54"H	10 Canister: 96"W x 20"D x 61"H, 12 Canister: 111"W x 20"D x 61"H, 14 Canister: 126"W x 20"D x 61"H, 16 Canister: 141"W x 20"D x 61"H
Agitation:	Bottom Electrical	Bottom Electrical	Bottom Electrical (Top Electrical-In-line)	Bottom Electrical (Top Electrical-In-line)	Top Electrical
Power:	110v 60Hz & 220v 50Hz	110v 60Hz & 220v 50Hz	110v 60Hz & 220v 50 or 60Hz	110v 60Hz & 220v 50 or 60Hz	110v 60Hz & 220v 50 or 60Hz
Warranty:	2 yrs. parts, 1yr. labor	2 yrs. parts, 1yr. labor	2 yrs. parts, 1yr. labor	2 yrs. parts, 1yr. labor	2 yrs. parts, 1yr. labor
Options:	—	169 oz. (5.3 quarts) Double-Capacity Canister	Quick-Release Canisters		Quick-Release Canisters
	—	—	Agitation Timer		Agitation Timer
	—	—	Countertop In-line Model		—
	—	—	Industrial Seals and Lids		Industrial Seals and Lids

34754-0812

For more information on how we can help increase your sales and productivity, call 800.462.2466.

Fluid Management Inc., 1023 Wheeling Rd., Wheeling IL 60090, f: 847.537.3221 www.fluidman.com

